


03 VOLUMETRIC GLASSWARE

DURAN® Volumetric Flask, class A, amber, batch certificate

with scribed graduation mark and ergonomic polyethylene stopper, white printed image, with batch certificate and certificate of conformity



ISO
1042

A
121 °C


Calibration is based on the poured in volume ("In") at a + 20 °C reference temperature. The volume content tolerances conform to accuracy class A, the accuracy limits of the German weights and measures regulations and DIN and ISO specifications.

Typical applications: precise measurement of specified liquid amounts, preparation and storage of standard solutions.

Cat. No.	Capacity (mL)	d (OD) (mm)	h (mm)	Neck	Stopper size	Accuracy limits (mL)	Remark	Pack Unit
246760954	5 W	22	70	9 ± 1	10/19	0.04	wide neck	2
246761059	10 W	27	90	9 ± 1	10/19	0.04	wide neck	2
246761256	20	39	110	9 ± 1	10/19	0.04		2
246761453	25	40	110	9 ± 1	10/19	0.04		2
246761753	50	50	140	11 ± 1	12/21	0.06		2
246762458	100	60	170	13 ± 1	12/21	0.1		2
246762552	100	60	170	13 ± 1	14/23	0.1		2
246763257	200	75	210	15.5 ± 1.5	14/23	0.15		2
246763651	250	80	220	15.5 ± 1.5	14/23	0.15		2
246764459	500	100	260	19 ± 2	19/26	0.25		2
246765455	1 000	125	300	23 ± 2	24/29	0.4		2
246766357	2 000	160	370	27.5 ± 2.5	29/32	0.6		2

DURAN® Volumetric Flask, class A, without certificate of conformity

with scribed graduation mark and octagonal stopper from PE, white printed image, with batch certificate, without certificate of conformity



ISO
1042

A
121 °C

Calibration is based on the poured in volume ("In") at a + 20 °C reference temperature. The volume content tolerances conform to accuracy class A, the accuracy limits of the German weights and measures regulations and DIN and ISO specifications.

Typical applications: precise measurement of specified liquid amounts, preparation and storage of standard solutions.

Cat. No.	Capacity (mL)	d (OD) (mm)	h (mm)	Neck	Stopper size	Accuracy limits (mL)	Remark	Pack Unit
216780704	5	22	70	7 ± 1	7/16	0.025		2
216780807	10	27	90	7 ± 1	7/16	0.025		2
216781203	20	39	110	9 ± 1	10/19	0.04		2
216781409	25	40	110	9 ± 1	10/19	0.04		2
216781709	50	50	140	11 ± 1	12/21	0.06		2
216782405	100	60	170	13 ± 1	12/21	0.1		2
216782508	100	60	170	13 ± 1	14/23	0.1		2
216783204	200	75	210	15.5 ± 1.5	14/23	0.15		2
216783607	250	80	220	15.5 ± 1.5	14/23	0.15		2
216784406	500	100	260	19 ± 2	19/26	0.25		2
216785402	1 000	125	300	23 ± 2	24/29	0.4		2
216786304	2 000	160	370	27.5 ± 2.5	29/32	0.6		2
216787309	5 000	215	475	38 ± 3	34/35	1.2		1